






Floating Sanitizing System Operating Instructions

 This is not a toy. For sanitizing hot tubs only!

FROG® @ease® is the hot tub sanitizing system* that takes the guess work out of water care so you always feel at ease while enjoying your hot tub.


FROG @ease Mineral Cartridge DIRECTIONS FOR USE: For use in hot tubs up to 600 gallons. Use with the FROG @ease SmartChlor Cartridge. Ensure all hot tub equipment is working properly. Operate the pump and filter as recommended by your hot tub manufacturer. Clean filter following manufacturer's directions. May be used with a previously filled hot tub unless it was sanitized with bromine or biguanides. Then drain and fill the hot tub with fresh water before using this product. **Start-up:** Balance the water according to the water balance guidelines with pH between 7.2 to 7.8 and total alkalinity at 80 to 120 ppm. Establish a free chlorine residual of 0.5 to 1.0 ppm with FROG Jump Start start-up or Softcare Dichlor approved chlorine following the directions for that product to establish the 0.5 to 1.0 ppm residual.

To assemble: **1.** Remove outer packaging. **2.** Align arrows on blue FROG @ease Mineral Cartridge and silver FROG @ease SmartChlor Cartridge. **3.** Push together and twist to lock. **4.** Set the dial on the chlorine cartridge (see Setting Chart in manual). **5.** Place entire system in the hot tub water. **6.** Use FROG Jump Start or Softcare Dichlor when replacing a FROG @ease SmartChlor Cartridge or once a month. **Replacing the Cartridges:** Replace the FROG @ease SmartChlor Cartridge when the system flips over. Follow label directions carefully. After four months or when draining and refilling the hot tub, replace the FROG @ease System that includes a FROG @ease Mineral Cartridge.


For complete instructions read the entire manual.

Step 1: Prepare the Softub Spa

1.



Fill hot tub with fresh water. If using source water that is high in iron or other metals, it may require the use of Softcare MetalGon.
2.



Clean or replace filter cartridges when dirty (Follow manufacturer's instructions).

3. Balance water by following STEPS a - d in order.


IMPORTANT: Always follow printed instructions on the balancing chemical packages. Add balancing chemicals in small increments one at a time with the jets on and wait 6 hours before testing again and adding any additional balancing chemicals.

Water Balance Guidelines	
pH:	7.2 – 7.8
Total Alkalinity:	80 - 120 ppm
Calcium Hardness:	150 - 250 ppm
Total Dissolved Solids:	<1500


a. Take a water sample from the hot tub and dip a FROG @ease Test Strip into it.



b. Look at the **Total Alkalinity** reading first. Adjustments should be made to bring the Total Alkalinity in the **range of 80 – 120 ppm** prior to making any adjustments to pH even if it throws pH off further.




c. After Total Alkalinity is in range, **test for pH**. It should be **between 7.2 and 7.8**. If higher or lower, add a pH adjuster.



d. Lastly **test for Calcium Hardness**. It should be **between 150 and 250 ppm**. If higher, partially drain the hot tub (about 6 inches) and fill with water low in calcium. If lower, add Calcium Balancer.


If balancing takes longer than 2 days use Jump Start or Softcare Dichlor to maintain a 0.5 to 1.0 ppm chlorine level while continuing balancing.

4.  **Very Important!** After balancing and before using cartridges, establish an initial residual of 0.5 - 1.0 ppm free chlorine with FROG® Jump Start® start-up, included in this package.

5. Heat water to the manufacturer's recommended temperature.

Active Ingredient: Silver Chloride0.5%
Other Ingredients:99.5%
Total:100.0%
KEEP OUT OF REACH OF CHILDREN CAUTION
It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Step 2: Put the System To Work in your Softub Spa



Simply follow these easy steps:

1.




Remove outer packaging from the FROG @ease SmartChlor Cartridge.
2.



Line up arrows on both cartridges, push together and twist to lock.


The FROG @ease Floating System has two replaceable cartridges.
Blue = FROG @ease Mineral Cartridge
Silver = FROG @ease SmartChlor Cartridge

The combination provides the Fresh Mineral Water benefits of cleaner, clearer and softer water that's easier to take care of.



Twist the dial on the FROG @ease SmartChlor Cartridge to the setting number for your hot tub. (See chart based on gallons).


4.



Toss into the hot tub. It will float in the water at a slight tilt.
- If you like, remove the FROG @ease System from the spa while soaking. Lift out the FROG @ease System and let drain into the hot tub. Place on any surface not susceptible to chlorine bleaching. Remember to return it to the hot tub afterwards.


Replacing Cartridges:

When the FROG @ease Floating System flips completely over, remove the FROG @ease SmartChlor cartridge.



FROG @ease SmartChlor Cartridge will last about 3-4 weeks for an average 300 gallon hot tub.

Floating System naturally **flips** in the water. To check if FROG @ease SmartChlor Cartridge is empty, lift up and drain all water from the system, then replace in the hot tub and see if it flips completely.



Detach FROG @ease SmartChlor Cartridge by twisting to align with “unlock” arrow and pull apart.

Attach new cartridge (see Step 2: Put the System to Work)




Discard in trash or offer for recycling if available.


Note: If the FROG @ease SmartChlor Cartridge still contains a small amount after detaching, place in hot tub to float on its own until empty. Do not let it sink to bottom as it may bleach hot tub surface.

Step 3: Routine Hot Tub Care


1.



Drain and refill hot tub as directed by your hot tub manufacturer or every four months when FROG minerals need to be replaced.
2.



Wipe areas above the waterline and on the inside surface of the cover when you use the tub and when check the water chemistry. Dampen a clean cloth with water from the spa. Wring the cloth outside the Softub
3.



Regularly test water with FROG @ease Test Strips and follow directions in Step 1 for maintaining pH, Total Alkalinity and Calcium Hardness.

NOTE: pH is affected by bather load, chemicals used, evaporation and the make-up of your source water so maintaining water balance regularly is important.

Troubleshooting

Cloudy Water or Low-Chlorine Levels

- Check water balance. pH and Total Alkalinity need to be in the proper ranges for the FROG @ease System to work correctly.
- Check FROG @ease SmartChlor Cartridge and replace if empty—see instructions under “Replacing Cartridges”.
- If FROG @ease SmartChlor Cartridge is not empty, turn dial setting up 1 number and monitor chlorine levels for a few days while maintaining water balance. If needed turn the dial up again.
- Check your calendar. The entire FROG @ease System, including the FROG @ease Mineral Cartridge, needs to be replaced every four months. Without the minerals, SmartChlor will not be enough to sanitize the hot tub.

FROG @ease SmartChlor Cartridge Life

- With significant bather load, you may require a higher dial setting which will shorten cartridge life.
- If you think the cartridge setting is too high, you can turn the dial setting down 1 number and monitor chlorine levels for a few days

while maintaining water balance. If needed, turn dial down again.

- Remove the FROG @ease System while using the hot tub with the jets running.

High Chlorine Levels



- This is highly unlikely with the FROG @ease System because SmartChlor is self-regulating. However, if you use standard test strips, it may appear that total chlorine is higher than the free chlorine.
- No worries—the strip is measuring the SmartChlor reserve, which will shift to free chlorine as needed. Please always use the FROG @ease Test Strips that were included with your System.

Learn more at frogproducts.com or call 800.222.0169
Register your FROG @ease Floating Sanitizing System at frogproducts.com



Manufactured by: King Technology
530 11th Ave S, Hopkins, MN 55343 U.S.A.
952-933-6118 • Customer Service 800-222-0169
FAX 952-933-2206 frogproducts.com

+ FROG @ease System consists of the FROG minerals silver chloride and carbonate used with 0.5 ppm of FROG @ease SmartChlor Cartridge. The FROG @ease Mineral Cartridge (EPA Reg. No. 53735-11) must be used in conjunction with the FROG @ease SmartChlor Cartridge (EPA Reg. No. 53735-14).
* Compared to the minimum ANSI recommended chlorine level of 2.0 ppm for a hot tub.
Made in U.S.A. Patents: kingtechnology.com/IP
EPA Est. No.: 64114-MN-1 E081418553091843R5N 20-48-0192